

4CRTR Rack Mount Receiver

Single or Dual RFoG Return Receivers



- Only 2 RU of Rack Space
- With Dual Units 24 Receivers in 2 RU
- Single Units 12 Receivers in 2 RU
- Usable down to -26 dBm
- EIN 1.75pA√Hz

843-347-4933

- Designed for RFoG
- Dual Power Supple Option
- Dual Units uses Digital Potentiometers
- Designed for RFoG low input levels

Specifications in Housing

Parameter	Test Conditions		Units	Notes	
Technology	-		-	-	SI/GaAs
Bandwidth	-		MHz	-	5-80/5-200
Response Flatness	-		dB	-	±0.5
Optical Wavelength	-		nm		1290-1620
Slope	-		dB	-	± 1
Minimum output	-27 dBm input		dB		10
Equalivlent Input Noise			EIN	Calculated	1.75pA√Hz
Minimum Light In	30 dB C/N		dBm	Measured	-26
Output Test Points	-		dB		-20 +/-1
Output Return Loss	Freq	5-200 MHz	dB		16

Single Receiver 4CRT \$299.00
Dual Receiver 4CRT-2 \$550.00
Rack 4CRAC-2U \$75.00
Power Supply 4CRSMPS12 \$100.00

Available now from stock to 4 weeks

Contact:

1256 Highway 501 Business

Conway SC 29526 sales@4cable.tv